

Estoform WB50

Water Based Mould Releasing Agent

Description

Estoform WB50 is specially blended of chemicals having release properties. It is supplied as a milky white coloured liquid.

Uses

It is specially designed to provide quick, clean and easy stripping of moulds and formworks.

Advantages

- Ensure stain-free concrete
- Water based is very suitable for timber moulds or formworks
- Most economical to use.
- Minimizes cleaning formworks

Physical Properties

Specific Gravity	0.9 – 1.0 at 25°C
Service Temperature	70°C max

Application Instructions

Application

All adherent materials must be removed prior to use.

Use brush, sponge or conventional mould oil sprayer to apply **Estoform WB50**. The correct nozzle size should be ensured, if a sprayer is used. Ponding or accumulation of excess mould oil should be avoided. It should be applied in a continuous even layer.

If there is a delay of application, the surface should be recoated. Non-absorbent surfaces shall be applied in a single layer only.

The moulds or formworks shall be clean before application of **Estoform WB50**.

Cleaning

The spillages of **Estoform WB50** should be absorbed into sand, earth or vermiculite and transfer to suitable container.

Packing & Size

Estoform WB50	200L / Drum
	20L / Pail

Coverage

Estoform WB50	13 to 26 m ² /litre, depend on type and porosity of timber formwork used
----------------------	---

Technical Support

Denka offers a comprehensive range of high performance, high quality of repair product for both new and existing concrete surfaces. In addition, the company offers a technical support package to specifies, end-users and contractors, as well as on-site technical assistance.

Storage

Estoform WB50 should be stored on pallets under dry conditions in original un-open drum. Under these conditions the product will have a shelf life of 12 months. If stored in extreme heat locations the shelf life may be reduced

Precaution

Estoform WB50 should not be swallowed and avoid to be in contact with skin or eyes. Wear gloves and goggles for protection. If swallowed, seek medical attention immediately

Do not induce vomiting.

The flammability risk of **Estoform WB50** is low. Adequate ventilation should be ensured when use. Do not use near naked fire or smoke during use.

240107

Additional Information

Denka Construction Solutions Malaysia Sdn Bhd offers a wide range of complementary products which includes waterstops, waterproofing products, grouts, anchors, specialized flooring products. In addition, a wide range of products formulated for repair and refurbishment of spalled concrete are available.



Denka Construction Solutions Malaysia Sdn Bhd
(591858-U)
No. 18, Jalan Utas 15/7, Seksyen 15,
40200 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: +603 5510 8810 Fax: +603 5518 8202
www.denka-cs.com

Limitation of Liability

The information contained in this brochure provides general advice for potential customers for DENKA about the basic properties and characteristics of various DENKA products (hereafter known as "the Product Information"). DENKA makes no warranty or representation as to the entire accuracy or completeness of the Product Information in the brochure. Nothing in this brochure will be deemed to create any express or implied warranty of merchantability, fitness for a particular purpose or infringement of any intellectual property rights. Each user of the Product Information and DENKA products assumes their own responsibility to properly determine the manner and suitability of use of the Product Information and DENKA products in its own operations. The user should exercise proper care in considering the Material Safety Data Sheet, Product Information and any other technical information provided by DENKA including descriptions of the conditions of use, warnings and other cautionary instructions. DENKA reserves the right to change the Product Information from time to time at its discretion and without notice.