

SAFETY DATA SHEET

1: IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product Name: **Estoflex Acryl 1000**
Application: Decorative Waterproofing Coating
Company: **Denka Construction Solutions Malaysia Sdn Bhd**
Address: No. 18, Jalan Utas 15/7, Seksyen 15, 40200 Shah Alam, Selangor
Telephone: 03 -55108810 Fax: 03 - 55100708

2: HAZARDS IDENTIFICATION

Type of product: Component / Mixture

A. Hazard Risk Classification

- Skin irritation/corrosion : Category 2
- Skin Sensitization : Category 1
- Serious eye damage/eye irritation : Category 2

B. Label elements including precaution statements.

- Symbol:



- Signal word: Danger
- Hazard Risk Statement
 - H315 Causes skin irritation
 - H317 May cause an allergic skin reaction
 - H319 Causes serious eye irritation

- Precautionary Statement

(Prevention)

- P201 Obtain special instruction before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapour spray
- P264 Wash your handling region thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required

(Response)

P363	Wash contaminated clothing before reuse.
P304 + 340 + P312	IF INHALE: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a doctor / physician if you feel unwell.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do not induce vomiting.
P302 + P352 + P333	IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice / attention.
P305 + P351 + P338 + P310	IN IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor / physician

(Storage)

P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

(Disposal)

P501	Dispose of contents / container in accordance to local/national regulations
------	---

3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No.	Content, %
Acrylic Emulsion	55965-84-9	30 – 40
Calcium Carbonate	14808-60-7	40 – 50
Water	7732-18-5	10 – 20
Defoamer	61791-28-4	0 – 5

All constituents of this product are listed in EINECS (European Inventory of Existing Commercial Chemical Substances) or EILINCS (European List of New Chemical Substances) or are exempt. Refer to Section 8 for Occupational Exposure Limits.

4: FIRST AID MEASURES

Description of first aid measure,

Eyes:	Do not rub eyes in order to avoid possible cornea damage at a result of mechanical stress. Incline head to injured eye, open the eyelid(s) widely and flush eye(s) immediately by thoroughly rinsing with plenty of clean water for at least 20 minutes to remove all particles. Remove contact lenses, if present and easy to do, continue rinsing. Avoid flushing particles into uninjured eye. Get immediately medical attention or consult physician.
Skin:	Wash skin with plenty of water. Remove contaminated clothing, footwear, watches etc. and clean thoroughly before re-using them. Seek medical attention if situation persist for rash and irritation.
Inhalation:	Move the person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention for discomfort or if coughing or other symptoms do not subside.
Ingestion:	Do not induce vomiting. If conscious, give plenty of water to drink. Get immediate medical attention or consult physician.

5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Carbon dioxide, powder, foam or water fog – Do not use water jets
Special Exposure Hazards:	No particular hazard known.
Special Protective Equipment:	Wear complete protective clothing including self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear suitable protective clothing, gloves and eye/face protection. Avoid airborne dust generation.
Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Soak up with inert absorbent or contain and remove by best available means. Gather into containers.

7: HANDLING AND STORAGE

Handling:	Avoid inhalation, skin and eye contact.
Storage:	Keep containers dry and tightly closed. Store in cool, dry areas. Protect from frost.

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:	None assigned.
Engineering Control Measures:	No specific ventilation requirement noted.
Personal Protective Equipment:	Impervious gloves (eg PVC). Safety glasses / Goggles. Plastic apron. Change contaminated clothing and clean before re-use.

9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Viscous Liquid
Colour:	Grey
Odour:	Slight
pH(concentrate):	7.0 – 8.5
Boiling Point/Range (°C):	100
Flash Point (closed, °C):	No data
Explosive Properties (%):	No data
Vapour Pressure (bar at 20°C):	No data
Relative Density (at 25°C):	1.30 - 1.40
Water Solubility:	Soluble.

10: STABILITY AND REACTIVITY

Stability:	Stable under normal temperature.
Material to avoid:	None known.
Condition to avoid:	Extremes of temperature and direct sunlight. Protect from freezing.
Hazardous Decomposition Products:	When polymer evaporates, polymer can burn and produce carbon monoxide, carbon monoxide and others product of combustion.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on a knowledge of the toxicity of the product's components:

Acrylic Emulsion

Acute toxicity-oral	LD50 Oral (Rat): >2000 – 10000 mg/kg. Virtually nontoxic after a single ingestion.
Skin contact	Not irritating to skin.
Eye contact	Not irritating to eyes.
Skin sensitization	May cause sensitization by skin contact.
Serious eye damage/irritation	Non-irritant
Germ cell-mutagenicity	Not mutagenic in bacteria.
Carcinogenicity	No indication of a carcinogenic effect.
Reproductive-toxicity	Not expected to cause reproductive toxicity.
STOT-single exposure	No specific target organ toxicity to be expected.
STOT-repeated exposure	No adverse effect was observed.

Calcium Carbonate

Acute toxicity	LD ₅₀ Oral (Rat): =500 mg/kg
Skin contact	Prolonged contact may cause redness and irritation.
Eye contact	Dust may cause mechanical irritation.
Ingestion	Ingestion may cause stomach discomfort.
Inhalation	Inhalation of dust in high concentration may cause irritation of respiratory system
Carcinogenicity	Crystalline silica dust is listed by IARC in Group 1 as known to cause lung cancer in human, if inhaled.
Reproductive-toxicity	Not expected to cause reproductive toxicity.

12: ECOLOGICAL INFORMATION

The following ecological assessment is based on a knowledge of the toxicity of the product's components:

Acrylic Emulsion

Ecotoxicity	Toxicity to fish: LC50 (96 h): >100 mg/l, Brachydanio rerio Aquatic Invertebrates: EC50 (48 h): >100 mg/l, Daphnia magna Aquatic plants: EC50 (72 h): >100 mg/l, Scenedesmus subspicatus Microorganism: EC20 (0.5 h): >100 mg/l, activated sludge
Mobility	Not available
Persistence/Degradability	>70% DOC reduction. Easily eliminated from water.
Bio-accumulative Potential	Not to be expected

Calcium Carbonate

Ecotoxicity	No data available
Persistence/Degradability	Not applicable – Inorganic chemical
Mobility	Insoluble in water
Bio-accumulative Potential	Not applicable – Inorganic chemical

13: DISPOSAL CONSIDERATIONS

Unused Product	Dispose of in accordance with local regulations. Do not empty into drains, sewers or water courses.
Used/Contaminated Product	Same as for Unused Product.
Packaging	May be steam cleaned and recycled.

14: TRANSPORT INFORMATION

IATA-DGR	Not classified as a dangerous good under transport regulations.
IMDG-Code	Not classified as a dangerous good under transport regulations.
ADR/RID	Not classified as a dangerous good under transport regulations.

15: REGULATORY INFORMATION

This product is NOT classified as dangerous for supply

Safety Phrases	Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
----------------	---

16: OTHER INFORMATION

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other application. Use of the product for applications other than as stated in this sheet may give rise to risks not mentioned in this sheet. The product should not be used than for the stated application or applications without seeking advice from Denka Construction Solutions Malaysia Sdn Bhd.

If this product has been purchased to a third party for use at work, it is the purchaser's duty to take all necessary steps to secure that any person handling or using the product is provided with information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of any hazards described to this sheet and of any precautions which should be taken. This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

SDS : Estoflex Acryl 1000
Date Issued : 14/07/2021
Revision : 03



Denka Construction Solutions Malaysia Sdn Bhd
(591858-U)

No. 18, Jalan Utas 15/7, Seksyen 15,
40200 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: +603 5510 8810 Fax: +603 5518 8202

www.denka-cs.com

Limitation of Liability

The information contained in this brochure provides general advice for potential customers for DENKA about the basic properties and characteristics of various DENKA products (hereafter known as "the Product Information"). DENKA makes no warranty or representation as to the entire accuracy or completeness of the Product Information in the brochure. Nothing in this brochure will be deemed to create any express or implied warranty of merchantability, fitness for a particular purpose or infringement of any intellectual property rights. Each user of the Product Information and DENKA products assumes their own responsibility to properly determine the manner and suitability of use of the Product Information and DENKA products in its own operations. The user should exercise proper care in considering the Material Safety Data Sheet, Product Information and any other technical information provided by DENKA including descriptions of the conditions of use, warnings and other cautionary instructions. DENKA reserves the right to change the Product Information from time to time at its discretion and without notice.